



SAFETY DATA SHEET

FIRWOOD 2502 ONE COAT WALL FINISH

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name FIRWOOD 2502 ONE COAT WALL FINISH

Product number 2502

Container size 5 litre container

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier Firwood Paints Ltd.
 Oakenbottom Road
 Bolton
 BL2 6DP
 T: +44 (0)1204 525231
 F: +44(0)1204 362522

Contact person e-mail: sales@firwood.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 1204 525231 (08.00-17.00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements EUH208 Contains METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6. May produce an allergic reaction.

Precautionary statements P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P501 Dispose of contents/ container in accordance with local regulations.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

FIRWOOD 2502 ONE COAT WALL FINISH

Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly closed original container in a dry, cool and well-ventilated place. Keep only in the original container.

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

TEXANOL (CAS: 25265-77-4)

DNEL

Workers, Industry/Professional - Inhalation; Long term : 49 mg/m³
 General population - ; : 14.5 mg/m³
 Workers, Industry/Professional - Dermal; Long term : 13.9 mg/kg/day
 General population - ; : 8.3 mg/kg/day
 - Oral; : 8.3 mg/kg/day

FIRWOOD 2502 ONE COAT WALL FINISH

PNEC	- Fresh water; 0.015 mg/l
	- Marine water; 0.0015 mg/l
	- Water, Intermittent release; 0.15 mg/l
	- Sediment (Freshwater); 0.17 mg/kg
	- Sediment (Marinewater); 0.017 mg/kg
	- Soil; 0.13 mg/kg

3-BUTOXYPROPAN-2-OL (CAS: 5131-66-8)

DNEL	Industry - Dermal; Long term : 44 mg/kg/day
	Industry - Inhalation; Long term : 270.5 mg/m ³
	Consumer - Dermal; Long term : 16 mg/kg/day
	Consumer - Inhalation; Long term : 33.8 mg/m ³

PNEC	- Fresh water; 0.525 mg/l
	- Marine water; 0.0525 mg/l
	- STP; 10 mg/l
	- Sediment (Freshwater); 2.36 mg/kg
	- Sediment (Marinewater); 0.236 mg/kg
	- Soil; 0.16 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Odour	Mild.
Initial boiling point and range	>100 @°C @ 760 mm Hg
Flash point	>100°C SCC (Setaflash closed cup).

FIRWOOD 2502 ONE COAT WALL FINISH

Relative density	1.1 - 1.5 @ 20°C
Solubility(ies)	Soluble in water.
Viscosity	700 - 1500 cP @ 25°C

9.2. Other information

Volatile organic compound This product contains a maximum VOC content of < 30 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing.
Ingestion	May cause discomfort if swallowed.
Skin contact	Liquid may irritate skin.
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.

Toxicological information on ingredients.

METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 64.0

Species Rat

ATE oral (mg/kg) 100.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 87.12

Species Rabbit

ATE dermal (mg/kg) 300.0

Acute toxicity - inhalation

FIRWOOD 2502 ONE COAT WALL FINISH

Acute toxicity inhalation (LC ₅₀ vapours mg/l)	0.33
Species	Rat
ATE inhalation (vapours mg/l)	0.33

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Ecological information on ingredients.

METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

M factor (Acute) 1

Chronic aquatic toxicity

M factor (Chronic) 1

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

FIRWOOD 2502 ONE COAT WALL FINISH

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). Control of Substances Hazardous to Health Regulations 2002 (as amended)
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Guidance	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

SECTION 16: Other information

Issued by	HS&E Manager.
Revision date	29/11/2016
Revision	6
Supersedes date	03/12/2015
SDS number	20445
SDS status	Approved.
Risk phrases in full	R36/38 Irritating to eyes and skin. Not classified.
Hazard statements in full	EUH208 Contains METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6. May produce an allergic reaction.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.