



SAFETY DATA SHEET

FIRWOOD 700 FAST DRY GLOSS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name FIRWOOD 700 FAST DRY GLOSS
Product number 700
Container size 5 & 25 litre containers

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier Firwood Paints Ltd.
 Oakenbottom Road
 Bolton
 BL2 6DP
 T: +44 (0)1204 525231
 F: +44(0)1204 362522

Contact person e-mail: sales@firwood.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 1204 525231 (08.00-17.00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226
Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Elicitation - EUH208 STOT SE 3 - H335 STOT RE 2 - H373
Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xn; R22, R48/20/21/22. Xi; R36/37/38. R10

Environmental The product is not expected to be hazardous to the environment.

Physicochemical Heating may generate flammable vapours. Vapours may form explosive mixtures with air.

2.2. Label elements

Pictogram



Signal word

Warning

FIRWOOD 700 FAST DRY GLOSS

Hazard statements	<p>H226 Flammable liquid and vapour. H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. EUH208 Contains C6-C19 BRANCHED FATTY ACIDS, COBALT (2+) SALTS. May produce an allergic reaction.</p>
Precautionary statements	<p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P314 Get medical advice/ attention if you feel unwell. P501 Dispose of contents/ container in accordance with national regulations.</p>
Contains	XYLENE
Supplementary precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 Ground/ bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour/ spray. P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P302+P352 IF ON SKIN: Wash with plenty of water. P312 Call a POISON CENTER/ doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P330 Rinse mouth. P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.</p>

2.3. Other hazards

SECTION 3: Composition/information on ingredients
--

3.2. Mixtures

FIRWOOD 700 FAST DRY GLOSS

XYLENE	30-60%
CAS number: 1330-20-7	EC number: 215-535-7
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) R10 Xn;R20/21 Xi;R38
DE-AROMATISED WHITE SPIRIT	5-10%
CAS number: 64742-47-8	EC number: 265-149-8
Classification Flam. Liq. 3 - H226 Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) Xn;R65. R10,R66.
BUTYL ACETATE -norm	1-5%
CAS number: 123-86-4	EC number: 204-658-1
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) R10 R66 R67
C6-C19 BRANCHED FATTY ACIDS, COBALT (2+) SALTS	<1%
CAS number: 68409-81-4	EC number: 270-066-5
Classification Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xn;R22. Xi;R38. N;R51/53. R43.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move affected person to fresh air at once. Get medical attention. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

FIRWOOD 700 FAST DRY GLOSS

Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Give plenty of water to drink. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is flammable. Heating may generate flammable vapours. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from oxidising materials, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep only in the original container.

Storage class Flammable liquid storage.

FIRWOOD 700 FAST DRY GLOSS

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m³(Sk)

DE-AROMATISED WHITE SPIRIT

Long-term exposure limit (8-hour TWA): OEL 1000 mg/m³

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

WEL = Workplace Exposure Limit

OEL = Occupational Exposure Limit.

Ingredient comments

WEL = Workplace Exposure Limits

XYLENE (CAS: 1330-20-7)

DNEL	Industry - Inhalation; Short term : 442 mg/m ³ Industry - Inhalation; Long term local effects: 221 mg/kg/day Industry - Dermal; Long term : 3182 mg/kg/day Consumer - Inhalation; Short term : 260 mg/m ³ Consumer - Inhalation; Long term : 65.3 mg/m ³ Consumer - Dermal; : 1872 mg/kg/day Consumer - Oral; Long term : 12.5 mg/kg/day
PNEC	- Fresh water; 0.327 mg/l - Marine water; 0.327 mg/l - Sediment (Freshwater); 12.46 mg/kg - Sediment (Marinewater); 12.46 mg/kg - Soil; 2.31 mg/kg - STP; 6.58 mg/l

DE-AROMATISED WHITE SPIRIT (CAS: 64742-47-8)

DNEL	Industry - Dermal; Long term : 300 mg/kg/day Industry - Inhalation; Short term : 1500 mg/m ³ Consumer - Dermal; Long term : 300 mg/kg/day Consumer - Inhalation; Long term : 900 mg/m ³ Consumer - Oral; Long term : 300 mg/kg/day
-------------	--

BUTYL ACETATE -norm (CAS: 123-86-4)

DNEL	Industry - Inhalation; Short term : 960 mg/m ³ Industry - Inhalation; Long term : 480 mg/m ³ Consumer - Inhalation; Short term : 859.7 mg/m ³ Consumer - Inhalation; Long term : 102.34 mg/m ³
-------------	---

FIRWOOD 700 FAST DRY GLOSS

PNEC	<ul style="list-style-type: none"> - Fresh water; 0.18 mg/l - Marine water; 0.018 mg/l - STP; 35.6 mg/l - Sediment (Freshwater); 0.981 mg/kg - Sediment (Marinewater); 0.0981 mg/kg - Soil; 0.0903 mg/kg
-------------	--

PROPYLENE CARBONATE (CAS: 108-32-7)

DNEL	<p>Industry - Inhalation; Long term systemic effects: 176 mg/m³</p> <p>Industry - Inhalation; Long term local effects: 20 mg/m³</p> <p>Industry - Dermal; Long term systemic effects: 50 mg/kg/day</p> <p>Consumer - Inhalation; Long term systemic effects: 43.5 mg/m³</p> <p>Consumer - Inhalation; Long term local effects: 10 mg/m³</p> <p>Consumer - Dermal; Long term systemic effects: 25 mg/kg/day</p> <p>Consumer - Oral; Long term systemic effects: 25 mg/kg/day</p>
PNEC	<ul style="list-style-type: none"> - Fresh water; 0.9 mg/l - Marine water; 0.09 mg/l - STP; 7.4E3 mg/l - Soil; 0.81 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Use protective gloves.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Organic vapour filter.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Odour	Aromatic.
Initial boiling point and range	137-143 @°C @ 760 mm Hg
Flash point	25°C CC (Closed cup).
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.8

FIRWOOD 700 FAST DRY GLOSS

Vapour density	>1
Relative density	0.9-1.20 @ @ 20°C
Solubility(ies)	Insoluble in water
Viscosity	300-420 mPas @ 25°C

9.2. Other information

Volatility	64
Volatile organic compound	This product contains a maximum VOC content of <525 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
-----------	--

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid	Avoid heat. Avoid contact with the following materials: Strong oxidising agents.
---------------------	--

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg)	530.0918654
------------------	-------------

Acute toxicity - dermal

ATE dermal (mg/kg)	1,337.43851479
--------------------	----------------

Acute toxicity - inhalation

ATE inhalation (gases ppm)	14,612.72387442
----------------------------	-----------------

ATE inhalation (vapours mg/l)	18.30084385
-------------------------------	-------------

Inhalation	Gas or vapour is harmful on prolonged exposure or in high concentrations.
Ingestion	Liquid irritates mucous membranes and may cause abdominal pain if swallowed.
Skin contact	Harmful in contact with skin. Prolonged or repeated exposure may cause severe irritation.
Eye contact	May cause severe eye irritation.
Target organs	Skin Eyes Respiratory system, lungs

SECTION 12: Ecological Information

Ecotoxicity	The product is not expected to be toxic to aquatic organisms.
-------------	---

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

FIRWOOD 700 FAST DRY GLOSS

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT

Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID label 3

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-E

FIRWOOD 700 FAST DRY GLOSS

Emergency Action Code 3YE

Hazard Identification Number (ADR/RID) 30

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). Control of Substances Hazardous to Health Regulations 2002 (as amended)
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Guidance	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

SECTION 16: Other information

Issued by	HS&E Manager.
Revision date	09/04/2015
Revision	7
Supersedes date	20/05/2014
SDS number	10248
SDS status	Approved.
Risk phrases in full	R10 Flammable. R20/21 Harmful by inhalation and in contact with skin. R22 Harmful if swallowed. R38 Irritating to skin. R43 May cause sensitisation by skin contact. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.

FIRWOOD 700 FAST DRY GLOSS

Hazard statements in full

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H373 May cause damage to organs (Respiratory system, lungs) through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
EUH208 Contains C6-C19 BRANCHED FATTY ACIDS, COBALT (2+) SALTS. May produce an allergic reaction.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.