

Water borne traffic line marking paint



Description A fast drying, water borne acrylic line marker. Quick and easy to apply and produces sharply defined edges. Good resistance to petrol, diesel, oil and water and excellent resistance to tyre pick up.

Recommended Use Suitable for use on both bare and previously painted concrete and asphalt surfaces.

Compliance Complies with "the VOC in Paints, Varnishes & Vehicle Refinishing Products Regulations 2005". EU limit value for this product (cat A/i): 140g / litre (2010)

Recommended Application Brush
Roller

Colour Range White, Green, Blue, Black & Yellow.

Physical Properties
VOC Content (as supplied) : max 70g / litre
Volume Solids : 35%
Mass of Solids : 48%
Flash Point : Not applicable

Drying Time @ 20°C
 Surface Dry - 30 mins
 Hard Dry - 1 hour
 Overcoat after 24 hours
 Drying times will be extended at low temperatures.
 Do not apply when ambient temperature falls below 10°C or relative humidity exceeds 85%.

Theoretical Coverage Rate *Rate 110 metres per litre on non absorbent surfaces @ 50mm line width.
Coverage rate can be affected by such variables as type and condition of substrate, type of application equipment and individual method of application.*

Thinners/Cleaner Use clean cold water.

Packaging
Pack Size : 5 litres
Weight : 1.15 - 1.30kg / litre (dependant on colour)
Shelf Life : 12 months from shipment date when stored in unopened, original containers.
Storage : Store in temperature range 5-40°C

Directions for use Ensure area to be coated is clean dry and sound. Do not apply to newly laid concrete. On previously unpainted concrete check for laitance and remove prior to coating with line marking paint.

Mask off area to be coated or use a template to get a straight edge. Mix product well before use. Apply by brush or mini roller. Remove masking tape immediately after application.

Cleaning

Clean application equipment with tap water before the coating has dried.

Health & SafetyRefer to Material Safety Data Sheet for information on correct handling and application of this product.



The information given on this sheet is, to the best of our knowledge, true and accurate. No guarantee of the results implied, or any loss or damage arising out of this material, however, are possible as the conditions of application are beyond our control. This is notwithstanding any liability arising from the Consumer Protection Act 1987 and the Health & Safety at Work Act. Health and Safety data is available on this product and should be referred to prior to its use.