

Chlorinated rubber finish



Description	A chlorinated rubber paint that provides good chemical and water resistance combined with a decorative effect.
Recommended Use	For use on surfaces likely to be exposed to weak/medium strength acids and alkalis. Also recommended for applications subject to a chemically laden atmosphere or in a coastal environment. Can be applied to both steel and concrete substrates.
Recommended Application Methods	Brush and roller (use as supplied or adjust with Firwood 143 Thinners). For application by airless spray contact Firwood for further information.
Gloss Level	Sheen finish
Colour Range	Full range of BS 4800, BS 381C & RAL shades except fluorescents and metallics.
Physical Properties	<u>VOC Content</u> (as supplied) : max 500g / litre <u>Volume Solids</u> : 38% <u>Mass Solids</u> : 60% <u>Flash Point</u> : 27°C
Drying Time @ 20°C	Surface dry - 30 mins. Hard dry - 90 mins. Drying times will be extended at low temperatures. Do not apply when ambient temperature falls below 3°C or relative humidity exceeds 90%.
Dry Film Thickness	20 - 30 µ
Wet Film Thickness	53 - 80 µ
Theoretical Coverage Rate	10 m ² per litre @ 25µ DFT <i>coverage rate can be affected by such variables as type and condition of substrate, type of application equipment and individual method of application.</i>
Thinners	Firwood 143 Thinners.
Packaging	<u>Pack Size</u> : 5 litres <u>Weight</u> : 1.2kg / litre <u>Shelf Life</u> : 2 years from shipment date when stored in unopened, original containers. <u>Storage</u> : Store in temperature range 5-40°C

Directions for use

All surfaces should be clean, dry and free from grease, rust and millscale.

Stir well before use.

For non-ferrous metals, a suitable etch primer is required.

Not suitable for spray application.

For further information contact our Technical Service Department.

Cleaning

Application equipment should be cleaned using Firwood 143 Thinners.

Health & Safety

Refer to Material Safety Data Sheet for information on correct handling and application of this product.



The information given on this sheet is, to the best of our knowledge, true and accurate. No guarantee of the results implied, or any loss or damage arising out of this material, however, are possible as the conditions of application are beyond our control. This is not withstanding any liability arising from the Consumer Protection Act 1987 and the Health & Safety at Work Act. Health and Safety data is available on this product and should be referred to prior to its use.

Data sheet Ref 680/3
Date of issue 25/08/15

Firwood Paints Ltd. Oakenbottom Road, Bolton, UK, BL2 6DP

T. +44 (0)1204 525231 **F.** +44 (0)1204 362522 **E.** sales@firwood.co.uk **W.** www.firwood.co.uk

Registered in England No.: 207861 Registered Office: Oakenbottom Road, Bolton, BL2 6DP